Research and Development

EPA/600/SR-97/116

November 1997



## **Project Summary**

## Air Emissions from the Treatment of Soils Contaminated with Petroleum Fuels and Other Substances

Bart Eklund, Stephen Roe, Patrick Thompson, Adrienne Inglis, Whitney Wheeless, and William Horton

The report updates a 1992 report that summarizes available information on air emissions from the treatment of soils contaminated with fuels. Soils contaminated by leaks or spills of fuel products, such as gasoline and jet fuel, are a nationwide concern. Air emissions during remediation are a potential problem because of the volatile nature of many of the fuel components and the remediation processes themselves, which may promote or result in contaminant transfer to the vapor phase. Limited information also is included on air emissions from the treatment of soils contaminated with hazardous wastes.

The report will allow staff from state and local regulatory agencies, as well as staff from EPA regional offices, to assess the different options for cleaning up soil contaminated with fuels. Seven general remediation approaches are addressed in this report. For each approach, information is presented about the remediation process, the typical air emission species of concern and their release points, and the available air emissions data. Control technologies for each remediation approach are identified, and their reported efficiencies are summarized. Cost data are given for each remediation approach and for its associated control technologies. Emission factors and other emission estimation procedures for each remediation approach are presented along with a brief case study.

This Project Summary was developed by the National Risk Management Research Laboratory's Air Pollution Prevention and Control Division, Research Triangle Park, NC, to announce key findings of the research project that is fully documented in a separate report of the same title (see Project Report ordering information at back).

## Introduction

The report updates a 1992 report that summarizes the available information on air emissions from the treatment of soils contaminated with fuels. It is intended to guide state and local air pollution control agencies in the evaluation of the air emission potential of treatment of contaminated soil and the cost-effectiveness of applicable emission control technologies. The scope was limited to the emissions of volatile organic compounds (VOCs); however, because of the limited data that were available, information was also included for the emission of other organic compounds. This additional information is primarily from the treatment of soils contaminated with hazardous wastes.

Seven general approaches for the disposal or treatment of soils contaminated with gasoline, oil, or diesel fuel were identified:

- Excavation and removal;
- · Thermal desorption;
- · Soil vapor extraction (SVE);
- In-situ biodegradation;
- Ex-situ (batch) biodegradation;
- · Incineration; and
- Soil washing/solvent extraction/soil flushing.

Information on excavation also is included because the *ex-situ* approaches

all require that the contaminated soil be excavated and fed to the treatment unit. The fugitive emissions from the materials handling operations for *ex-situ* processes often are overlooked or ignored, but they may represent a significant fraction of the total emissions from the remediation effort.

Each general approach may include several specific options. For example, thermal desorption may be performed in portable units designed specifically for soil treatment or in rotary drum aggregate dryers that are part of asphalt plants or other industrial facilities.

Literature pertaining to the emissions of VOCs for each remediation approach was

identified and reviewed. The summarized information was organized into the same 10-part format for each approach:

- · Process description;
- Identification of air emission points;
- Identification of typical air emission species of concern;
- Summary of published air emissions data:
- Identification of applicable control technologies;
- Cost data for the overall remediation approach;
- · Cost data for the emission controls:
- Equations and models for estimating VOC emissions;

- Case study of the use of the remediation approach; and
- · References.

Information about each remediation technology is summarized in Table 1. A variety of control devices may be employed with each of the remediation technologies. The most commonly used controls for each technology are shown in Table 2.

An uncertainty and sensitivity analysis was also performed for equations and models presented for estimating emissions. A range of emissions was predicted based on the variability of the parameters used in the equations/models. Parameters having the greatest influence on the predicted emissions were identified.

Table 1. Summary of Information for Remediation Technologies

Remediation Technology	Emission Points	Typical Air Emission Species of Concern	Amount of Air Emissions Data	Frequency of Use of Controls	Comments
Excavation	Soil Surface	VOCs, PM	Very limited	Seldom	Often overlooked, Potential to be major air emission source
Thermal Desorption	Stack, Waste feed	VOCs, SVOCs	Extensive	Always	Usually performed with mobile units
Soil Vapor Extraction	Stack	VOCs	Some	>50% of systems	May be converted to bioventing after initial period
In-situ Bioremediation	Stack, Soil surface	VOCs, Degradation products	Very limited	Seldom (rarely needed)	Being used/proposed with increasing frequency
Ex-situ Bioremediation	Open tanks, Waste feed	VOCs, Degradation products, PM from waste feed	Very limited	Seldom	
Incineration	Stack, Waste feed	Metals, PM, NO <sub>x</sub> , CO, Dioxins/furans	Very extensive	Always	Seldom first choice for soils contaminated with fuels
Soil Washing	Process unit, Waste feed	VOCs	None	Not known	Developing technology
Solvent Extraction	Process unit, Waste feed	VOCs,	None	Not known	Developing technology
Soil Flushing	Soil surface, Water recovery	VOCs	None	Seldom (rarely needed)	Developing technology

Table 2. Typical Control Technologies used for Remediation Technologies Particulate Matter VOCs/SVOCs Acid Gases Emission Source and Metals Materials Handling: Excavation NA Operational Controls Water Sprays Foams Enclosure Storage Piles Polymer Sheeting Cover NA Wind Screen Transport Vehicles Cover Cover NA Foam Roadways NA Gravel/Paving NA Water Sprays Water Sprays with Additives Cyclone Wet Scrubber Thermal Desorption Condensers Venturi Scrubber Thermal Incineration Dry Scrubber Fabric Filter Carbon Adsorption HEPA Filter Soil Vapor Extraction Carbon Adsorption NA NA Catalytic Incineration Thermal Incineration Internal Combustion Engine In-situ Bioremediation Carbon Adsorption NA NA Ex-situ Bioremediation Carbon Adsorption NA NA Incineration NA Cyclone Wet Scrubber Venturi Scrubber Dry Scrubber Ionizing Wet Scrubber Wet ESP Fabric Filter Soil Washing Carbon Adsorption NA NA Solvent Extraction Thermal Incineration NA NA

NA

NA

Carbon Adsorption

Soil Flushing

B. Eklund, P. Thompson, A. Inglis, W. Wheeless, and W. Horton are with Radian Corp., Austin, TX 78720; and S. Roe is with E. H. Pechan & Associates, Inc., Rancho Cordova, CA 95742

Susan A. Thorneloe is the EPA Project Officer (see below).

The complete report, entitled "Air Emissions from the Treatment of Soils Contaminated with Petroleum Fuels and Other Substances," (Order No. PB98-111685; Cost: \$57.00, subject to change) will be available only from:

National Technical Information Service

5285 Port Royal Road Springfield, VA 22161 Telephone: 703-487-4650

The EPA Project Officer can be contacted at:

Air Pollution Prevention and Control Division National Risk Management Research Laboratory U.S. Environmental Protection Agency

Research Triangle Park, NC 27711

United States Environmental Protection Agency Center for Environmental Research Information Cincinnati, OH 45268

Official Business Penalty for Private Use \$300

EPA/600/SR-97/116

BULK RATE POSTAGE & FEES PAID EPA PERMIT No. G-35